

Charisma Super Slim Cassette



www.carriercca.com



Charisma Super Slim Cassette



FEATURES:

- Compact Design, Super Slim Body Size
- 360° Airflow Panel is standard
- Fresh Air In-take
- External Duct Capability feature
- Remote Control

SPECIFICATION FOR SLIM CASSETTE

Models			42TNC0182002301*	42TNC0242002301*	42TNC0362002302*	42TNC0482002302*	42TNC0602002301*
Power supply	V-Hz-Ph		220-230V/60Hz/1Ph	220-230V/60Hz/1Ph	220-230V/60Hz/1Ph	220-230V/60Hz/1Ph	220~230/60Hz/1Ph
Cooling Capacity	Btu/h		18000	24000	36000	48000	60000
Indoor fan motor	Qty		1				
	Speed (Hi/Med/Lo)	RPM	580/510/430	780/600/550	780/600/550		
Indoor coil	Number of rows		2	2	2	3	3
	Fin spacing	mm	1.4				
	Fin type		Hydrophilic aluminium				
	Tube outside dia.and type	mm	7mm				
Indoor air flow(Hi/Med/Lo)	m ³ /h		1100/820/700	1600/1250/1100	1673/1189/1065	1828/1334/1223	2000/1700/1500
Indoor noise level (sound pressure)(Hi/Med/Lo)	dB(A)		47/43/39	50/47/44	53/47/45.5	52/46/45.5	54/50/45
Indoor unit	Dimension (W x Dx H) (body)	mm	840x840x205	840x840x245	840x840x245	840x840x287	840x840x287
	Packing (W x Dx H) (body)	mm	900x900x225	900x900x265	900x900x265	900x900x292	900x900x292
	Dimension (W x Dx H) (panel)	mm	950x950x55				
	Packing (W x Dx H) (panel)	mm	1035x1035x90				
	Net/Gross weight (body)	kg	23/26.4	25.6/29.4	26/31	30/35	29/34
	Net/Gross weight (panel)	kg	5/8				
Drain connection	mm		ODφ32				
Refrigerant piping	Liquid side/Gas side	mm (inches)	φ6.35/φ12.7 (1/4 1/2")	φ9.52/φ15.9 (3/8"/5/8")	φ9.52/φ19 (3/8"/3/4")		

*Panel is sold separately under model PCK-MBQ-02C1-010



Authorized Dealer