

Xperience3

Experience the Comfort



www.carriercca.com

Carrier

turn to the experts™





Xperience3

- Compact design
- Multi position
- Auto-swing in both directions
- Auto-cool-dry-heat-fan
- 3 speed fan
- On/off timer
- Left or right drain pipe connection
- Wireless remote control
- R410A /R22 refrigerant

INDOOR MODEL			42KUE036N-1	42KUE048N-1	42KUE060N-1
Power supply		V-ph-Hz	220~230-1-60	220~230-1-60	220~230-1-60
Cooling	Capacity	Btu/h	36000	48000	60000
	Input	W	3874	4930	6199
Indoor air flow(Hi/Med/Lo)		m3/h	1722/1459/1281	2367/1942/1687	2548/2104/1790
Indoor noise level (sound pressure)(Hi/Med/Lo)		dB(A)	53/49/46.5	55.5/50/46	57/52/48.5
Indoor unit	Dimension (WxDxH)	mm	1285x675x235	1650x675x235	1650x675x235
	Packing (WxDxH)	mm	1360x755x313	1725x755x313	1725x755x313
	Net/Gross weight	kg	32/37	39/46	42/48
Design pressure		MPa	4.2/1.5	4.2/1.5	4.2/1.5
Drainage water pipe diameter		mm	ODΦ25mm	ODΦ25mm	ODΦ25mm
Refrigerant piping	Liquid side/Gas side	mm(inch)	Φ9.52/Φ19(3/8"/3/4")	Φ9.52/Φ19(3/8"/3/4")	Φ9.52/Φ22(3/8"/7/8")
Controller			Remote control	Remote control	Remote control
Operation temperature		°C	17~30	17~30	17~30
Room temperature	Cooling	°C	17~32	17~32	17~32
	Heating	°C	/	/	/
Qty/per 20' /40' /40'HQ (indoor unit)			92/188/213	72/147/167	72/147/167



Authorized Dealer